

ESSENTIAL

Floortex



BUDGET
FRIENDLY



SEMI-LOOSE LAY
UP TO 20 M²



HIGH QUALITY
TEXTILE BACKING



5 YEARS
WARRANTY

Technical information / Technische informatie - Information technique - Technische Daten

Usage class / Gebruiksklasse - Classe d'usage - Eignungsklasse	EN ISO 10874	22
Total thickness / Totale dikte - Epaisseur totale - Gesamtdicke	EN ISO 24346	ca. 2,00 mm
Wear layer / Slijtlaag - Couche d'usure - Nutzschicht	EN ISO 24340	ca. 0,20 mm
Wear layer treatment / Behandeling slijtlaag - Traitement couche d'usure - Schutz vor Schmutz		Natural Feel
Total weight/m² / Totaal gewicht/m² - Poids total/m² - Gewicht/m²	EN ISO 23997	ca. 1.310 g/m²
Width / Breedte - Largeur - Breite		2 - (3) - 4 m
Standard length / Standaardlengte - Longueur standard - Standardlänge		ca. 30 - (30) - 30 m
Weight of standard roll / Standaard rolgewicht - Poids standard des rouleaux - Standardrollengewicht		ca. 78,6 - (117,9) - 157,2 kg
Inflammability / Brandklasse - Classement feu - Brandverhalten	EN 13501-1	Cfl-S1
Slip resistance / Antislip - Glissance - Rutschfest	EN 13893	DS
Slip restraint / Slipweerstand - Résistance au glissement - Rutschemmung	EN 16165 Annex B	R10
Thermal conductivity / Thermische geleidbaarheid - Conductivité thermique - Wärmeleitfähigkeit	ISO 8302 (1991)	0,0667 W/mK
Heat insulation / Thermische isolatie - Isolation thermique - Wärmedurchlasswiderstand	EN 12667:2001-01	0,0338 m² K/W
Acoustic insulation / Contactgeluidsisolatie - Isolation acoustique - Trittschallverbesserungsmaß	EN ISO 717-2	17 dB
Underfloor heating / Vloerverwarming - Chauffage par le sol - Fußbodenheizung	EN 12524 EN 12667	Suitable - Geschikt Adapté - Geeignet
Resistance to household chemicals / Bestendigheid tegen huishoudelijke chemicaliën Résistance aux produits d'entretien domestiques - Haushaltschemikalienbeständigkeit	EN ISO 26987	Very good - Zeer goed Très bon - Sehr gut
Warranty years / Garantie in jaren - Durée de la garantie en années - Garantie Jahren		5

The warranty covers manufacturing defects and early wear due to normal residential use. / Wij bieden u garantie tegen fabrieksfouten en vroegtijdige slijtage bij normaal residentieel gebruik.
/ La garantie couvre les erreurs de fabrication et l'usure précoce lors d'un emploi normal résidentiel. / Die Garantie gewährleistet Fabrikationsfehler und frühzeitiges Abnutzen in normalen Wohnbereich.



EN 14041
19 - DOP - V541
resilient floor covering
EN ISO 26986



A BRAND OF
UNILIN

